

LG Hausys floors

1. Introduction

An effective maintenance program protects your new resilient flooring and will provide years of performance. Maintenance should be performed according to foot traffic, temperature, etc. Although general maintenance programs should be performed, customized programs set to unique conditions should be followed to maximize the results and the overall life of the floor.

Understanding flooring and unique conditions for maintenance is necessary. Especially maintenance program for commercial areas should be considered before installation. Floor finish products for LG Hausys Harmony, Advance Tile are as follows. Descriptions of the products are based on the manufacturer's technical information.

For more details of product information, refer to the label attached on the back of the products or consult with the manufacturer.

2. Safety Measures after Installation

Remove dirt and other foreign materials. Adhesive residues must be removed immediately with damp mop or cloth. If the adhesive has already cured, remove them using mineral spirits or denatured alcohol on a clean, white cloth.

Newly installed flooring must not have foot traffic for at least 24 – 48 hours. Do not clean the floor during this time. Minimize foot traffic.

Water cleaning may cause notable decrease in adhesion strength.

Placing furniture or heavy objects within 24 hours after the installation may leave permanent indentations on the floor surface.

CAUTION

Wet floors can cause accidents. Slippery floors due to improper maintenance may cause slip and fall accidents.

3. LG HAUSYS LVT Maintenance

1) Initial Maintenance

- ① Remove dirt and other foreign materials thoroughly with vacuum or broom.
- ② Dilute cleaning solution following the manufacturer's dilution ratio recommendations. Damp mop the floor, being careful not to flood the floor with excess water.
- ③ Stubborn areas should be allowed to soak for 5~10 minutes then have the excess moisture mopped off of the floor.
- ④ For better results, use an auto scrubber or a 175 rpm swing machine with a blue or red pad. Do not use a black or brown pad.

LG Hausys floors

- ⑤ Soak leftover residues.
- ⑥ Damp mop with a rinse pad. Soak the rinse residues completely and wait until it dries.
- ⑦ Follow all instructions as written on the bottle.
- ⑧ Wait until the floor is completely dry. Drying time is usually 20 – 30 minutes. You may double coat for the best effect. Second coating must be done after the first coating has completely dried.

2) Regular Maintenance

- ① Vacuum and / or sweep often to prevent dirt build up or scratches.
- ② Mix cleaning solution and water according to dilution ratio as recommended by the manufacturer.
- ③ Damp mop the floor.

Additional cleaning may be necessary for hard to clean or stubborn areas. Always clean and rinse with clean water.