



SONATA | WOOD & STONE LUXURY VINYL TILES & PLANKS

Sonata

Sonata wood & stone

Sonata[®] will have everyone singing the praises with its line of 2.5 mm luxury vinyl tiles and planks with a 20 mil wear layer. Developed for medium to heavy commercial use, the collection comes in a timeless and elegant line of wood planks and stone designs.

The line also features an aluminum oxide polyurethane surface treatment for superior scratch and stain protection. With Sonata, architects and designers now have everything they need to create beautiful, affordable, long-lasting flooring that's music to everyone's ears.

CEO-01 Light Grey | CEO-03 Dark Grey Plank size: 9" x 48"

FEATURES & BENEFITS

LA

- Commercial grade LVT makes it suitable for high traffic areas.
- Aluminum oxide polyurethane surface treatment offers superior scratch and stain protection.
- No-wax-for-life flooring that can be easily cleaned and disinfected, limiting the spread of infections.
- Tiles available in traditional 18" x 18" and contemporary 12" x 24" formats.
- Planks available in 4" x 36",
 6" x 48" and 9" x 48" formats.
- FloorScore[®] certified.
- Industry-wide EPD.
- LEED[®] v4 Eligible MR & EQ Credits.
- Quick-Ship program available.

EUROPEAN WALNUT Plank size: 6" x 48"



BURGHAL ZEBRAWOOD Plank size: 6" x 48"





CABIN MAPLE



SAPELE MAHOGANY Plank size: 6" x 48"



COUNTRY OAK



NORDIC CHERRY



TIMELESS TRAVERTINE Tile size: 18" x 18"



RUSTIC SLATE



CRS-06 Dark Grey

CRS-01 Light Grey

METRO STRANDS







CMS-01 Taupe

COSMO STONEWOOD



URBAN STONE





SONATA® | WOOD & STONE

Gauge		0.098"	2.50 mm
Size		18" x 18"	457 mm x 457 mm
		12" x 24"	305 mm x 610 mm
		4" x 36"	102 mm x 915 mm
		6" x 48"	152 mm x 1219 mm
		9" x 48"	229 mm x 1219 mm
Product Classific			
ASTM F 1700	Solid Vinyl Floor Tile		Class III, Type A or B
Wear Layer Thickness		0.020"	0.5 mm
ASTM D 2047	Static Coefficient of Friction (leather)		≥ 0.5
ASTM D 3389	Abrasion Resistance (H-22, 500 g @ 1,000 cycles)		PASS
ASTM E 648	Critical Radiant Flux CRF (W/cm ²)	≥ 0.45	
ASTM E 662	Smoke Density	≤ 4 50	
ASTM F 925	Chemical Resistance		Exceeds
ASTM F 970	Static Load (modified at 2,500 psi)	≤ 0.005"	
ASTM F 1514	Heat Stability	$\Delta E \le 8.0$	
ASTM F 1515	Light Stability	$\Delta E \le 8.0$	
ASTM F 1914	Indentation	Residual < 8%	
ASTM F 2055	Squareness		0.010" maximum
Indoor Air Quality (IAQ)		FloorScore Certified by SCS Certification	
Volatile Organic Compounds (VOC's)		Registration Number SCS-FS-03325	
Maintenance		No wax for life, easy maintenance	
PU (Polyurethane) surface treatment containing Aluminum Oxide		Facilitates maintenance	
Adhesives	PS-30		Regular traffic
	AD-535		Heavy traffic/rolling loads
Limited Wear Warranty		10 years for commercial installations 20 years for residential installations	

Please note that technical website documents prevail.

® / SONATA is a registered trademark of American Biltrite.

american-biltrite.com



American Biltrite, 200 Bank Street, Sherbrooke, Quebec, Canada J1H 4K3 To order samples: flooring@american-biltrite.com | 1.800.437.8743 | Fax 1.800.810.5731 | Technical Services: 1.800.479.0190



® / SONATA is a registered trademark of American Biltrite.

american-biltrite.com

American Biltrite, 200 Bank Street, Sherbrooke, Quebec, Canada J1H 4K3 To order samples: flooring@american-biltrite.com | 1.800.437.8743 | Fax 1.800.810.5731 | Technical Services: 1.800.479.0190

Printed in Canada BRO-EO-SON Issued: 12/2020