



AmericanBiltrite
Flooring



ABMARATHON® | Round | Hammered | Slate

TILES & STAIR TREADS

ABMARATHON®

Main Street 251 22 475

32 Street Level
42 Avenue B-Ped Level

Central Station

E

Index

4

Introduction

6

ABMARATHON®
Round & Slate Tiles
Round Stair Treads

10

ABMARATHON®
Hammered Tiles
& Stair Treads

12

ABDEFENDER®
Tiles & Stair Treads

16

Sustainability
American Biltrite
Legacy

20

Technical
Specifications

ABMARATHON®

A rubber flooring collection that is not afraid to be stepped on.

Available in tile format featuring round, hammered and slate profiles as well as stair treads.

- > Made for high traffic environments
- > Made in North America
- > Declare Red List Free
- > Floorscore® certified for best indoor air quality


Improved vulcanized rubber formula.

- > Easier to clean
- > Improved stain resistance
- > Improved color stability, less shades

Made to last for the most demanding environments for over 45 years.

- > High traffic commercial applications
- > Industrial applications
- > Sports venues
- > Transit industry
- > Education
- > Governmental and municipal
- > Parks & Recreation
- > Corporate office
- > Retail

Also available: ABDEFENDER®
Your first line of defense meeting special fire protection requirements.
▶ See page 12 for details.



If your goal is to select **carbon- neutral materials**, ABMARATHON® can be produced with renewable natural gas made from organic waste, which reduces greenhouse gases at the source.



ABPURE®, ABMARATHON® and ABDEFENDER® rubber flooring products are **Red List Free** and part of the Living Building Challenge **Declare** Program.

Declare.



What is Declare?

The program provides a clear and informative label for building products and supports the Living Building Challenge's Red List for material transparency and toxic chemical avoidance as well as simplifying material specification and project certification.

What is the Red List and what does it mean to be Red List Free?


The Red List represents the “worst in class” materials, chemicals, and elements known to pose serious risks to human health and the greater ecosystem. For a product to be awarded Red List Free status means that it does not contain any ingredients on the Living Building Challenge Red List.

To learn more about the Living Building Challenge, visit www.living-future.org/lbc.

ABMARATHON® TILES

ABMARATHON® Rubber Flooring gives modern expression to timeless, geometric and organic profiles for high traffic applications.

- > 3 mm thickness in 18"x18" and 36"x36" nominal size tiles and coordinated stair treads in both round and hammered profiles
- > Superior traction
- > Superior comfort underfoot properties
- > Superior footfall sound absorption




- > Naturally antimicrobial and antifungal properties
- > Micro-ground straight edges for a perfect seamless look
- > The only rubber flooring that is Declare Red List Free, free of crystalline silica and formaldehyde
- > Carbon-neutral option available on special order

ABMARATHON® Slate Profile (MCA)


ABMARATHON® Slate Profile (MCA) comes standard in 4 colors with a 3 mm thickness and 36"x36" nominal size.




MCA-33 POLISHED PEWTER
LRV 24.7



MCA-36 TAN
LRV 31.7



MCA-91 NIGHT SKY
LRV 6.5



MCA-37 CARRIAGE GREY
LRV 8.3

AB**MARATHON**® Round Profile (MCR) Comes in 18"x18" & 36"x36" nominal sizes.

Cool Greys



MCR-33
POLISHED PEWTER
LRV 24.7




MCR-24
BATTLE GREY
LRV 10.1



MCR-20
MIDNIGHT BLACK
LRV 5.1



MCR-31
GAINESBORO VALLEY
LRV 57.5



MCR-22
SPY GREY
LRV 11.2


Warm Greys



MCR-30
SAND CASTLE
LRV 54.9



MCR-36
TAN
LRV 31.7



MCR-38
WARM STONE
LRV 20.8




MCR-37
CARRIAGE GREY
LRV 8.3




Beiges & Browns




MCR-43
SMOKEY BEIGE
LRV 43.3



MCR-46
BAKED EARTH
LRV 30.7



MCR-48
DEEP CHESTNUT
LRV 8.5



MCR-58
EXPLORE RED
LRV 8.4


Neutral Blues




MCR-96
LAKE BLUE
LRV 16.5




MCR-91
NIGHT SKY
LRV 6.5



MCR-85
EQUILIBRIUM GREEN
LRV 18.6



MCR-88
ECO GREEN
LRV 32.3




MCR-87
FOREVER GREEN
LRV 10.8


Power Hues




MCR-95
QUEBEC BLUE
LRV 10.1



MCR-94
NEW GEN BLUE
LRV 17.8



MCR-77
CHUMMY ORANGE
LRV 42.1



MCR-54
RED DU JOUR
LRV 15.2



MCR-65
VIOLET RIOT
LRV 10.0

35" 11/16 × 35" 11/16 (906 mm × 906 mm) 17" 13/16 × 17" 13/16 (452 mm × 452 mm)

THICKNESS: 3 mm (0.118")

To order tiles in Round profile, use MCR code followed by color code and size. Example: MCR-38 in 18"x18".

ABMARATHON® ROUND STAIR TREADS

ABMARATHON® Round Stair Treads are made to be stepped on day in and day out, going up or going down. They offer all the technical features required for the most demanding environments:

- > Superior traction
- > Comfort underfoot
- > Available in regular or one-piece solution that includes the tread, the riser, and the nosing
- > In 36", 48" and 72" wide formats
- > With or without visually impaired strips
- > Available in 12 colors that coordinate with ABMARATHON® Round tiles (refer to color chart on page 7)
- > Red List Free and part of the Living Building Challenge® Declare® Program



Carborundum Strips

These strips can be added to your stair treads for added traction and as visual aids.



VIT-82 NIGHTGLOW



VIT-72 YELLOW



VIT-22 BLACK




VIT-52 RED



VIT-15 WHITE



Stair Tread System





REGULAR
STAIR TREADS
(RTR)





STAIR TREADS
WITH RISER
(OPR)



REGULAR STAIR TREADS
FOR THE VISUALLY
IMPAIRED
(RVR)



STAIR TREADS WITH RISER
FOR THE VISUALLY
IMPAIRED
(OVR)



TO ENSURE DURABILITY, AMERICAN BILTRITE STAIR FILLER SHOULD BE USED UNDER THE NOSING OF THE STAIR TREADS DURING INSTALLATION.



To order ABMARATHON® round stair treads

- 1** Select the type of stair tread: Use the product codes shown above, e.g.: **OVR**.
- 2** Select your color: Refer to the ABMARATHON® Round colorways with stair tread symbol for colors available, e.g.: **OVR-33**.
- 3** Select your width: e.g.: **OVR-33-48**.
- 4** If applicable, add the carborundum strip color (for visually impaired) by selecting the first digit of the color code of the strips (for example, the red strip item code is 5), e.g.: **OVR-33-485**. ▶ See page 8 for codes.

| ABMARATHON® ROUND STAIR TREADS | 36" | 48" | 72" |
|---|------------|------------|------------|
| REGULAR | RTR-XX-36 | RTR-XX-48 | RTR-XX-72 |
| WITH RISER | OPR-XX-36 | OPR-XX-48 | OPR-XX-72 |
| REGULAR WITH VISUALLY IMPAIRED STRIPS | RVR-XX-36X | RVR-XX-48X | RVR-XX-72X |
| WITH RISER WITH VISUALLY IMPAIRED STRIPS | OVR-XX-36X | OVR-XX-48X | OVR-XX-72X |

ABMARATHON® HAMMERED TILES AND STAIR TREADS

ABMARATHON® tiles in hammered profile are 3 mm thick and available in 18"x18" in 9 colors with coordinated stair treads.



MCH-33 POLISHED PEWTER
LRV 24.7




MCH-24 BATTLE GREY
LRV 10.1



MCH-20 MIDNIGHT BLACK
LRV 5.1



MCH-22 SPY GREY
LRV 11.2



MCH-38 WARM STONE
LRV 20.8



MCH-37 CARRIAGE GREY
LRV 8.3



MCH-96 LAKE BLUE
LRV 16.5





MCH-91 NIGHT SKY
LRV 6.5





MCH-85 EQUILIBRIUM GREEN
LRV 18.6

ABMARATHON® Hammered tiles come standard in 18"x18" format using item code: MCH- followed by color number.



REGULAR
STAIR TREADS
(RTH)





STAIR TREADS
WITH RISER
(OPH)



REGULAR STAIR TREADS
FOR THE VISUALLY
IMPAIRED
(RVH)



STAIR TREADS WITH RISER
FOR THE VISUALLY
IMPAIRED
(OVH)



TO ENSURE DURABILITY, AMERICAN BILTRITE STAIR FILLER SHOULD BE USED UNDER THE NOSING OF THE STAIR TREADS DURING INSTALLATION.

To order
ABMARATHON®
hammered
stair treads

- 1** Select the type of stair tread: Use the product codes shown above, e.g.: OVH.
- 2** Select your color: Refer to the ABMARATHON® Hammered colorways, e.g.: OVH-33.
- 3** Select your width: e.g.: OVH-33-48.
- 4** If applicable, add the carborundum strip color (for visually impaired) by selecting the first digit of the color code of the strips (for example, the red strip item code is 5), e.g.: OVH-33-485. ▶ See page 8 for codes.

| ABMARATHON® HAMMERED STAIR TREADS | 36" | 48" | 72" |
|---|------------|------------|------------|
| REGULAR | RTH-XX-36 | RTH-XX-48 | RTH-XX-72 |
| WITH RISER | OPH-XX-36 | OPH-XX-48 | OPH-XX-72 |
| REGULAR WITH VISUALLY IMPAIRED STRIPS | RVH-XX-36X | RVH-XX-48X | RVH-XX-72X |
| WITH RISER WITH VISUALLY IMPAIRED STRIPS | OVH-XX-36X | OVH-XX-48X | OVH-XX-72X |

ABDEFENDER®

Did you know?

Emergency exit stairways of high buildings require rubber stair tread and flooring material to meet ASTM E84 Tunnel Test Class A and CAN/ULC S102.2. This is in order to limit hazards to buildings and their occupants in case of a fire emergency.

Materials that meet these stringent norms are considered extremely fire resistant, to be a slower smoke and fire spread hazard, and ultimately made to protect occupants and buildings in case of emergency.

In the U.S. the requirements for material used for emergency and fire exits may vary from city, state, local, and federal government agencies and may require non-combustible building materials that meet the same requirements of the International Building Code and Canadian building codes requirements.



**Be on the safe side, specify
ABDEFENDER®, a high fire-retardant
flooring and stair tread system.**


Selecting **ABDEFENDER®** rubber floor tiles and stair treads is your first line of defense for emergency exit stairways of high buildings requiring superior fire-retardant properties and low smoke development.

- > Increased safety due to high fire-retardant properties and low smoke development
- > Designed to meet the requirements of emergency exits, egress areas and stairways of high buildings
- > Meets ASTM E84 Standard Test Method for Surface Burning Characteristics of Building Materials - Class "A"
- > Meets CAN/ULC S102.2 Test of Surface Burning Characteristics of Building with ratings of Flame-Spread (≤ 25), and Smoke Developed (≤ 50).

Available in 3 mm gauge Tiles and Stair Tread with Round profiles.

- > **ABDEFENDER®** Stair Treads & Tiles are available in 6 colors
- > Tiles come standard in round profile (ADR) in 18"x18" and 36"x36" nominal sizes.


Colors




ADR-33 POLISHED PEWTER
LRV 25.3



ADR-24 BATTLE GREY
LRV 10.3




ADR-91 NIGHT SKY
LRV 6.7



ADR-38 WARM STONE
LRV 21.3



ADR-37 CARRIAGE GREY
LRV 8.7




ADR-20 ONYX BLACK
LRV 3.8

To order tiles, use ADR code followed by color code and size. Example: ADR-33 in 18"x18".



ABDEFENDER® STAIR TREADS

- > ABDEFENDER® Stair Treads are available in 48" and 72" widths
- > Comes standard with integrated risers with or without visually impaired strips

STAIR TREADS
WITH RISER
(PTR)



STAIR TREADS
WITH RISER
FOR THE VISUALLY
IMPAIRED
(PVR)




TO ENSURE DURABILITY, AMERICAN BILTRITE STAIR FILLER SHOULD BE USED UNDER THE NOSING OF THE STAIR TREADS DURING INSTALLATION.

To order
ABDEFENDER®
stair treads

- 1** Select with or without visually impaired strips (comes standard in one single piece with integrated riser), e.g.: **PVR**.
- 2** Select your color: Refer to the ABDEFENDER® colorways, e.g.: **PVR-33**.
- 3** Select your width: e.g.: **PVR-33-48**.
- 4** If applicable, add the carborundum strip color (for visually impaired) by selecting the first digit of the color code of the strips (for example, the red strip item code is 5), e.g.: **PVR-33-485**. ▶ See page 8 for codes.

| ABDEFENDER® STAIR TREADS | 48" | 72" |
|---|------------|------------|
| WITH RISER | PTR-XX-48 | PTR-XX-72 |
| WITH RISER WITH VISUALLY IMPAIRED STRIPS | PVR-XX-48X | PVR-XX-72X |



Custom Colors

Available for AB**DEFENDER**®
and AB**MARATHON**® collections.

Let your brand do the talking.

Work with our color lab to create on-demand colors to match your institution's brand or to achieve your design vision. The minimum quantity requirement of 2,200 sqft can be used between tiles and stair treads and multiple profiles.

Contact your sales representative to discuss your design vision and program.

SUSTAINABILITY ACHIEVEMENTS



JEAN-PIERRE BENOIT
CORPORATE VICE PRESIDENT
AND GENERAL MANAGER

Situated in the Eastern Townships, our team is privileged to enjoy the great outdoors daily, surrounded by picturesque lakes, national parks, and ski resorts. We set ourselves the highest standards of corporate citizenship and continuously improve our goals year after year. This dedication is deeply ingrained in our history and legacy. We prioritize both environmental stewardship and the well-being of our employees.



Reduction of natural gas & greenhouse gas emissions

- Reduction of 7,000 tons of greenhouse gas
- Equivalent of a car's emissions driving 45 times around Earth or 4.5 times to the moon and back!



Water usage reduction

- Reduction of 340,000 m³ of water
- Equivalent of 120 Olympic pools!



Electricity usage reduction

- 5 GW*h reduction
- The equivalent of 5 months of electricity for our office and factory



Reduction of landfill waste and increase of recycling of manufacturing waste

- Reduction of 3,500 tons of manufacturing waste
- The equivalent of 700,000 mud flaps
- Projects:
 - Recycling vinyl waste into other manufactured products and matting products
 - Recycling rubber material into mud flaps

If your goal is to select carbon neutral materials, **ABMARATHON®** can be produced with renewable natural gas (RNG) made from organic waste, that reduces greenhouse gases at the source.



By manufacturing **ABMARATHON®** with RNG, American Biltrite is investing in local initiatives to reduce carbon emissions at the source and achieving carbon neutrality in product manufacturing.


1



Waste

Instead of letting organic waste go to landfills where they would release greenhouse gases, the organic waste from industrial, commercial, agricultural and even residential activities are collected.


2



Biomethanation
& Purification

This organic waste is transported to biomethanation farms where it is fermented to generate a gas that is then purified, to become a renewable natural gas made from 100% organic waste.

3



RNG is used
by our facility

We can use the full amount of renewable natural gas made from 100% organic waste to offset **ABMARATHON®**'s cradle-to-gate carbon footprint, as measured in its life cycle analysis (LCA).




World-wide patent pending **full circle recycling technology** into new products

American Biltrite, a true innovator for the planet, has developed a groundbreaking manufacturing technology that allows for the recycling of rubber after it has been cured. This technology enables post-manufacturing waste of any cured rubber product to be recycled back into new production without affecting its physical properties or visual attributes. Under conventional production methods, rubber that has been fully cured cannot be reshaped through a second curing process, making this innovative technology exceptionally unique.

By recycling post-manufacturing waste into new products, this innovation helps decrease landfill waste. Furthermore, it opens the potential for developing circular economy business models with our customers.

American Biltrite is also the manufacturer of the market's leading and most loved solid vinyl tile: **Texas Granite®**.

The floor that never needs waxing to stay beautiful.



Each year, we lovingly craft
our signature Teddy Bear
with meticulous attention to
detail, bringing joy and smiles
to countless young children.



RODERICK (2024)



American Biltrite Legacy

- A third-generation family-owned American business
- Over 250 plant, office, and research and development employees dedicated to rubber and flooring manufacturing
- Rubber factory established in 1913
- Local distribution and customer service team
- One of the only rubber sheet flooring products made in North America
- Reliable supplier:
 - Considered an essential product manufacturer for the healthcare, transport, and pharmaceutical industries
 - Remained in operation during the COVID-19 pandemic with no disruption in supply chain
 - Made it through two World Wars, the Great Depression, and the Spanish flu

Made in
**North
America**
since 1913



TECHNICAL SPECIFICATIONS

ABMARATHON® | RUBBER TILE FLOOR

TECHNICAL SPECIFICATIONS

| | | |
|--|--|---|
| GAUGE | <u>Metric</u> 3 mm | <u>Imperial</u> 0.118" |
| SIZES | 906 mm x 906 mm 452 mm x 452 mm Micro Ground™ | 35.687" x 35.687" 17.798" x 17.798" Micro Ground™ |
| PRODUCT CLASSIFICATION | | |
| ASTM F1344 | Rubber Tile Floor | Type I, A or B (Homogeneous) |
| ASTM D2047 | Static Coefficient of Friction (leather/Neolite) | ≥ 0.5 |
| ASTM D3389 | Abrasion Resistance (H-18 500 g @ 1,000 cycles) | Pass |
| ASTM E648 | Critical Radiant Flux CRF (W/cm²) | ≥ 0.45 |
| ASTM E662 | Smoke Density | ≤ 450 |
| ASTM F925 | Chemical Resistance | Meets requirements (details upon request) |
| ASTM F970 | Static Load | ≤ 0.005" |
| ASTM F1514 | Heat Stability | ΔE ≤ 8.0 |
| ASTM G21 | Antimicrobial Resistance Test | Pass (28 days) |
| INDOOR AIR QUALITY (IAQ) VOLATILE ORGANIC COMPOUNDS (VOC'S) | FloorScore® Certified by SCS Certification Registration Number SCS-FS-01492 | |
| ADHESIVES | AD-777 AD-590 | Regular traffic Heavy rolling loads |
| LIMITED WEAR WARRANTY | 10 years | |

ANTIMICROBIAL

IMPORTANT: All ABMARATHON® rubber flooring, through its composition and without the use of antimicrobial chemicals, does not promote microbial growth.

Please note that technical website documents prevail.

® ABMARATHON is a registered trademark of American Biltrite.

ABMARATHON® | RUBBER STAIR TREADS

TECHNICAL SPECIFICATIONS

TREADS: REGULAR ROUND/HAMMERED & REGULAR/HAMMERED ROUND WITH VISUALLY IMPAIRED SAFETY STRIP

| GAUGE | <u>Metric</u> | <u>Imperial</u> |
|---------------|------------------------------------|-----------------------------------|
| | Round: 3.17 mm Hammered: 3.5 mm | Round: 0.118" Hammered: 0.140" |
| SIZES | 0.914 m | 36" |
| | 1.219 m | 48" |
| | 1.828 m | 72" |
| DEPTH | 314 mm | 12-3/8" |
| NOSING DEPTH | 47 mm ADA compliant | 1-7/8" ADA compliant |
| NOSING RADIUS | 6 mm ADA compliant | 1/4" ADA compliant |

TREADS & RISERS: ONE-PIECE ROUND/HAMMERED & ONE-PIECE ROUND/HAMMERED WITH VISUALLY IMPAIRED SAFETY STRIP

| GAUGE | <u>Metric</u> | <u>Imperial</u> |
|---------------|------------------------------------|-----------------------------------|
| | Round: 3.17 mm Hammered: 3.5 mm | Round: 0.118" Hammered: 0.140" |
| SIZES | 0.914 m | 36" |
| | 1.219 m | 48" |
| | 1.828 m | 72" |
| DEPTH | 482 mm | 19" |
| NOSING DEPTH | 47 mm ADA compliant | 1-7/8" ADA compliant |
| NOSING RADIUS | 6 mm ADA compliant | 1/4" ADA compliant |

PRODUCT CLASSIFICATION

| | | |
|--|--|---|
| ASTM F2169 | Standard Specification for Resilient Stair Treads | Type TS Rubber Vulcanized Thermoset – Class 2, Group 1 & 2 (Visually Impaired Safety Strip) |
| ASTM D2047 | Static Coefficient of Friction (leather/Neolite) | ≥ 0.5 |
| ASTM E648 | Critical Radiant Flux CRF (W/cm²) | ≥ 0.45 |
| ASTM E662 | Smoke Density | ≤ 450 |
| ASTM F925 | Chemical Resistance | Meets requirements (details upon request) |
| ASTM F1514 | Heat Stability | ΔE ≤ 8.0 |
| ASTM G21 | Antimicrobial Resistance Test | Pass (28 days) |
| INDOOR AIR QUALITY (IAQ) VOLATILE ORGANIC COMPOUNDS (VOC'S) | FloorScore® Certified by SCS Certification Registration Number SCS-FS-01492 | |
| ADHESIVES | AD-777, AD-590 & Zip-Step® | Regular traffic |
| NOSING COMPOUND | NC-888 | Regular traffic |
| LIMITED WEAR WARRANTY | 10 years | |

ANTIMICROBIAL

IMPORTANT: All ABMARATHON® rubber flooring, through its composition and without the use of antimicrobial chemicals, does not promote microbial growth.

Please note that technical website documents prevail.

® ABMARATHON and Zip-Step are registered trademarks of American Biltrite.

ABDEFENDER® | RUBBER STAIR TREADS & TILES

TECHNICAL SPECIFICATIONS

| STAIR TREADS | TREADS & RISERS | ONE-PIECE ROUND & ONE-PIECE ROUND WITH VISUALLY IMPAIRED SAFETY STRIP |
|--|--|---|
| PROFILES | Round | |
| GAUGE | 3.17 mm | 1/8" |
| SIZES | 0.914 m 1.219 m 1.828 m | 36" 48" 72" |
| DEPTH | 314 mm | 19" |
| NOSING DEPTH | 47 mm ADA compliant | 1-7/8" ADA compliant |
| NOSING RADIUS | 6 mm ADA compliant | 1/4" ADA compliant |
| TILE PROFILES | Round | |
| GAUGE | 3 mm | 0.118" |
| SIZES | 904 mm x 904 mm 451 mm x 451 mm Micro Ground™ | 35.600" x 35.600" 17.755" x 17.755" Micro Ground™ |
| PRODUCT CLASSIFICATION | | |
| ASTM F2169 | Standard Specification for Resilient Stair Treads | Type TS Rubber Vulcanized Thermoset – Class 2, Group 1 & 2 (Visually Impaired Safety Strip) |
| ASTM F1344 | Rubber Tile Floor | Type 1, A or B (Homogeneous) |
| ASTM D2047 | Static Coefficient of Friction (leather / Neolite) (TILE) | ≥ 0.5 |
| ASTM 3389 | Abrasion Resistance (H-18,500 g @ 1,000 cycles) (TILE) | Pass |
| ASTME84 | Surface Burning Characteristics | Class A |
| ASTM E648 | Critical Radiant Flux CRF (W/cm²) | ≥ 0.45 |
| ASTM E662 | Smoke Density | ≤ 450 |
| ASTM F925 | Chemical Resistance | Meets requirements (details upon request) |
| ASTM F970 | Static Load (TILE) | ≤ 0.005" |
| ASTM F1514 | Heat Stability | ΔE ≤ 8.0 |
| ASTM G21 | Antimicrobial Resistance Test (TILE) | Pass (28 days) |
| CAN/ULC S102.2 | Surface Burning Characteristics | FSV ≤ 25 and SDV ≤ 50 |
| INDOOR AIR QUALITY (IAQ) VOLATILE ORGANIC COMPOUNDS (VOC'S) | FloorScore® Certified by SCS Certification Registration Number SCS-FS-01492 | |
| ADHESIVES | AD-777, AD-590 & Zip-Step® (STAIR TREADS) | Regular traffic |
| NOSING COMPOUND | NC-888 (STAIR TREADS) | Regular traffic |
| LIMITED WEAR WARRANTY | 10 years | |

ANTIMICROBIAL

IMPORTANT: All ABDEFENDER® rubber flooring, through its composition and without the use of antimicrobial chemicals, does not promote microbial growth.

Please note that technical website documents prevail. Custom colors available on special request with minimum order quantity.

® ABDEFENDER and Zip-Step are registered trademarks of American Biltrite.



® / ABMARATHON, ABDEFENDER are registered trademarks of American Biltrite.

american-biltrite.com



American Biltrite, 200 Bank Street, Sherbrooke, Quebec, Canada J1H 4K3
To order samples: flooring@american-biltrite.com | 1-800-437-8743 | Fax 1-800-810-5731 | Technical Services: 1-800-479-0190

Printed in Canada BRO-E5-MAR Issued: 04/2025