




367000

Couture


– classic softness from the world of fashion

The silky-soft and exclusive velour quality is a true classic with exceptional acoustic properties due to its short, upright pile. Couture has found its name in the world of fashion, where velour is cherished from Paris to Copenhagen for its inherent tactility, weight, and extravagance, which adds a wondrous radiance to any garment and design.

Available in 16 tailor-made colours. Special colours from +200 m². Felt backing from +200 m².




367050



367050



367100



367150



367160



367200



367250




367280



367300




367350




367390




367450




367600




367630



367650



367780



328330

Technical data

	Standard	 Broadloom w/Textile	 Broadloom w/Felt	 Tiles
Type of Manufacture	ISO 2424	Tufted 1/10"		
Structure	ISO 2424	Heat-set Velour		
Pile material	ISO 2424	100% PA66		
Dye method		Continuous dyed		
Primary backing	ISO 2424	PP		
Secondary backing	ISO 2424	rPET Textile		
 Dimension/Width	ISO 3018	Approx. 400 cm		
Surface pile thickness	ISO 1766	Approx. 9.00 mm		
 Total thickness	ISO 1765	Approx. 11.00 mm		
Total pile mass	ISO 2424	Approx. 1,150 g/m ²		
 Total mass	ISO 8543	Approx. 2,200 g/m ²		
Stitch rate	ISO 1763	Approx. 160,000 /m ²		
 Antistatic	ISO 6356	≤ 2 kV		
 Classification for use	EN 1307	23 Domestic - Intensive		
 Classification for use	EN 1307	31 Commercial - Moderate		
 Luxury rating class	EN 1307	LC4		
 Castor chair suitability	EN 985	Intensive use		
 Stair suitability	EN 1963	Occasional use		
 Impact sound reduction	ISO 10140	Approx. ΔL _w 26 dB		
 Thermal resistance	ISO 8302	Approx. 0.147 m ² K/W		
 Fireclass	EN 13501-1	C _{fl} -s1		

Certifications

	Standard	 Broadloom w/Textile	 Broadloom w/Felt	 Tiles
CE	EN 14041	0809-CPR-19006044-C2		
DOP	EN 14041	1118#19006044-C		
IACG	EN 16516	Compliant		
M1		Compliant		
Reach		Compliant		
BREEAM NOR		Compliant		
Recycled content		100% recycled backing		



As we continuously improve our products and testing procedures, any above declaration is subject to amendments without prior notice.
For the latest technical specifications, installation and maintenance guide visit:

www.yorkshore.com