

PlayTiles®

by dinoflex

Let Kids be Kids

SCHOOLS ■ PARKS ■ PLAYGROUNDS ■ DAYCARES



**RECYCLED
RUBBER
FLOORING**

Dinoflex PlayTiles® creates a safe place to let kids be kids. Parents will have peace of mind knowing their kids are playing on an ASTM certified surface. Specially designed to reduce injuries from falls, kids can run, jump, swing, and slide on a product that supports play.



Water
Permeable
and Slip
Resistant.

Tough enough to stand up to any weather condition and the most active children, PlayTiles® allow your kids to play on a dry surface after a rainstorm, getting them back outside quickly.

Features

- Fall height certified
- High traction
- Water permeable
- Molded tile creates solid surface
- Easy to install
- Long lasting
- Meets ADA standards

Benefits

- Reduces injuries from falls
- Slip resistant even when wet
- Pours in nature, allows water to flow through
- No adhesive required for most applications
- Tiles can be installed in any season
- Withstands any wear and tear
- Creates an inclusive play space for all

Best For

Climbing Walls

Community Centers

Daycares

Indoor Play Areas

Recreation Centers

Schools



Color: Forest Green

Interlocking Tile

24" x 24" | 4ft²

(61cm x 61cm = 0.37m²)


THICKNESS	FALL HEIGHT	With 1 ¼" Dinofall System	With 2 ¼" Dinofall System
1 1/2" (38mm)	4' (1.2m)	7' 6"	11' 6"
2 1/4" (57mm)	6' (1.8m)	9'	12'

Interlocking System

Dinoflex self-aligning interlocking system provides for a fast and accurate installation. Interlocking tubes are included with every order for a nominal cost.



Interlock Tube



Interlocking Panels



Tile Back

Ramps and Wedges



1.5" Wedge



2.25" Wedge



Inside Corner



Outside Corner



1.5" ADA Wheelchair Ramp



2.25" Wheelchair Ramp
(Sold as a set)

Dinofall System

Increase fall height protection by using our Dinofall System made from 100%, recycled, non-contaminated, post industrial cross-linked closed cell polyethylene.

Dinofall Dimensions

THICKNESS

1 1/4" and 2 1/4"

31.75mm and 57.15mm

SHEET

39 1/16" x 90 9/16"


99.21cm x 230.02mm

Tolerance +/- 1/16"

Tolerance +/- 0.06mm



Tile




Dinofall



Tile and Dinofall

Color Swatches



BLUE EMBER



FOREST GREEN



STONE BEIGE



TEAK BROWN




RED




BLACK

EPDM Variations



25% BLUE



25% GREEN




25% BEIGE




25% BROWN




25% RED



25% ORANGE




50% BLUE



50% GREEN



50% BEIGE




50% BROWN




50% RED




50% ORANGE




75% BLUE



75% GREEN




75% BEIGE



75% BROWN



75% RED



75% ORANGE

Contact your Sales Representative for more information.
Colors show are reproduced as closely as possible to actual product.
Contact Dinoflex for product sample.



Click here to design your own
Recycled Rubber Tile.

DESCRIPTION	TEST METHOD	RESULT
Fall Height	ASTM F1292	1½" - 4 ft 2¼" - 6 ft
Fall Height (with 1¼" Dinofall system)	ASTM F1292	1½" - 7.5 ft 2¼" - 9 ft
Fall Height (with 2¼" Dinofall system)	ASTM F1292	1½" - 11.5 ft 2¼" - 12 ft
Freeze Thaw	ASTM C67	No Change
Slip Coefficient	ASTM C1028	Dry: 0.81 Wet: 0.73
Rubber Deterioration in an Air Oven	ASTM D573	No change
Critical Radiant Flux	ASTM E648	CRF 0.10 watts/square cm (2¼" - Black)
Critical Radiant Flux - With Fire Retardant	ASTM E648	CRF 1.04 watts/square cm (1½" Black 100% Fire Retardant) CRF 0.84 watts/square cm (1½" Black 60% Fire Retardant) CRF 0.99 watts/square cm (1½" Black with Fire Retardant top) CRF 0.95 watts/square cm (2¼" Black with Fire Retardant)
Critical Radiant Flux - With Fire Retardant (15 min burn)	ASTM E648 (NY)	CRF 1.04 watts/square cm (1½" Black 100% Fire Retardant) CRF 1.04 watts/square cm (1½" Black 60% Fire Retardant) CRF 0.99 watts/square cm (1½" Black with Fire Retardant top) CRF 0.97 watts/square cm (2¼" Black 100% Fire Retardant whole tile) CRF 0.97 watts/square cm (2¼" Black with Fire Retardant)
Mildew Resistance	ASTM G21	21 days - light mold growth 28 days - moderate mold growth
Water Drainage		4 litres drained in 306.71 seconds (5.1 minutes)
Wind Resistance	UL 1897	Pass

Please Note: All measurements are subject to nominal variation.

Yorkshire Commercial Interiors
A BuildDirect Company
3551 W 1st St
Sanford, FL 32771

Tel: 866-996-7563
Yorkshire@Yorkshire.com
yorkshire.com

**10 year
Limited Warranty**

when installed in accordance with
Dinoflex's Installation Guidelines.

Date Issued: Nov 24 2022

