



393180




393100




393120




393150




393180




393340




393350




393380




393450




393260




393300




393320




393330




393550



393660



393750



393850

393000 / T393000

Ex-Dono Quartet

– a rich diversity of life

Ex-Dono Quartet is a contract carpet that combines durability and good acoustic properties with natural poetry. The coarse pile is tufted in a staggered pattern, full of artistic nerve and details, as if the carpet were a meadow in all its poetic being with flowers and grasses together creating a diversity of life.

Available as broadloom and as square carpet tiles in 16 classic colours. Special colours from +200 m². Felt backing from +200 m².

Ex-dono Quartet

393000 / T393000



Technical Data

	Standard	Broadloom w/Textile	Broadloom w/Felt	Broadloom w/Foam	Tiles
Type of Manufacture	ISO 2424	Tufted 1/10"	Tufted 1/10"	Tufted 1/10"	Tufted 1/10"
Structure	ISO 2424	Loop pile	Loop pile	Loop pile	Loop pile
Pile material	ISO 2424	100% PA66	100% PA66	100% PA66	100% PA66
Dye method		Continuous dyed	Continuous dyed	Continuous dyed	Continuous dyed
Primary backing	ISO 2424	PET non woven	PET non woven	PET non woven	PET non woven
Secondary backing	ISO 2424	rPET Textile	rPET Felt	Foam	TEXtiles®
Dimension/Width	ISO 3018	Approx. 400 cm	Approx. 400 cm	Approx. 400 cm	50 x 50 cm (5m ² /box)
Surface pile thickness	ISO 1766	Approx. 4.00 mm	Approx. 4.00 mm	Approx. 4.00 mm	Approx. 4.00 mm
Total thickness	ISO 1765	Approx. 6.00 mm	Approx. 7.00 mm	Approx. 7.00 mm	Approx. 7.50 mm
Total pile mass	ISO 2424	Approx. 620 g/m ²	Approx. 620 g/m ²	Approx. 620 g/m ²	Approx. 620 g/m ²
Total mass	ISO 8543	Approx. 2,100 g/m ²	Approx. 2,600 g/m ²	Approx. 2,400 g/m ²	Approx. 3,200 g/m ²
Stitch rate	ISO 1763	Approx. 169,500 /m ²	Approx. 169,500 /m ²	Approx. 169,500 /m ²	Approx. 169,500 /m ²
Antistatic	ISO 6356	≤ 2 kV	≤ 2 kV	≤ 2 kV	≤ 2 kV
Classification for use	EN 1307	23 Domestic - intensive use	23 Domestic - intensive use	23 Domestic - intensive use	23 Domestic - intensive use
Classification for use	EN 1307	33 Commercial - heavy use	33 Commercial - heavy use	33 Commercial - heavy use	33 Commercial - heavy use
Luxury rating class	EN 1307	LC2	LC2	LC2	LC2
Dimensional stability	EN 986	-	-	-	≤ 0.2 %
Castor chair suitability	EN 985	Intensive use	Intensive use	Intensive use	Intensive use
Stair suitability	EN 1963	Intensive use	Intensive use	Intensive use	Intensive use
Impact sound reduction	ISO 10140	Approx. ΔL _w 25 dB	Approx. ΔL _w 27 dB	Approx. ΔL _w 27 dB	Approx. ΔL _w 25 dB
Sound absorption	EN ISO 354				Approx. 0.20 α _w
Thermal resistance	ISO 8302	Approx. 0.10 m ² K/W	Approx. 0.11 m ² K/W	Approx. 0.11 m ² K/W	Approx. 0.11 m ² K/W
Fireclass	EN 13501-1	C _{fl} -s1	C _{fl} -s1	B _{fl} -s1	B _{fl} -s1

Recommended tile installation



Square







Ex-dono Quartet

393000 / T393000



Certifications

	Standard	 Broadloom w/Textile	 Broadloom w/Felt	 Broadloom w/Foam	 Tiles
CE	EN 14041	0809-CPR-19006044-C2	0809-CPR-19006044-C2	0809-CPR-19006044-C9	0809-CPR-19006044-C6
DOP	EN 14041	1118#19006044-C2	1118#19006044-C2	1118#19006044-C9	1118#19006044-C6
IACG	EN 16516	Compliant	Compliant	Compliant	Compliant
M1		Compliant	Compliant	Compliant	Compliant
PEF - LCA Scope 3 CO ₂ - Eq according to EU PEF Standard		12,0 kg CO ₂ - Eq	12,0 kg CO ₂ - Eq	12,0 kg CO ₂ - Eq	12,0 kg CO ₂ - Eq
Reach		Compliant	Compliant	Compliant	Compliant
BREEAM NOR		Compliant	Compliant	Compliant	Compliant
Recycled content		100% recycled backing	100% recycled backing	-	100% recycled backing



As we continuously improve our products and testing procedures, any above declaration is subject to amendments without prior notice.
For the latest technical specifications, installation and maintenance guide visit:

www.yorkshore.com

Yorkshore Commercial Interiors
3551 W 1st St Sanford, FL 32771
866-996-7563 | Yorkshore@Yorkshore.com