

T8000000000

Art Weave


– raw, patinated, and artistic structures

Art Weave by Fletco® is created from a vision of combining the raw, patinated look of an industrial floor with the unique acoustic properties of a flat-woven carpet. The four different designs in the modular collection are inspired by both natural and man-made materials such as stone and concrete, and are digitally printed on the durable surface, where the raw motifs gain an extra dimension in the form of the underlying weave structure.

Available in four selected designs, four different shapes, and a variety of organic colours.



800001300




800001250




800001300



800001320



800009150



800009170



800009300



800009350



800009450



800006200



800006300



800006380



800002150



800002250



800002300



















800002320

Art Weave by Fletco®

T800000 - Weave TEXTiles® series



Technical data

	Standard	 Broadloom w/Textile	 Broadloom w/Felt	 Tiles
Type of manufacture	ISO 2424			Woven
Structure	ISO 2424			Loop pile
Pile material	ISO 2424			100% PET Anvire FR®
Dye method				Print
Primary backing	ISO 2424			PET
Secondary backing	ISO 2424			TEXTiles®
 Dimensions/Width	ISO 3018			By order
Surface pile thickness	ISO 1766			Approx. 2.20 mm
 Total thickness	ISO 1765			Approx. 5.00 mm
Total pile mass	ISO 2424			Approx. 575 g/m ²
 Total mass	ISO 8543			Approx. 3,300 g/m ²
Stitch rate	ISO 1763			Approx. 164,000 /m ²
 Antistatic	ISO 6356			≤ 2 kV
 Classification for use	EN 1307			23 Domestic - Heavy
 Classification for use	EN 1307			33 Commercial - Heavy
 Luxury rating class	EN 1307			LC1
 Dimensional stability	EN 986			≤ 0,2 %
 Castor chair suitability	EN 985			Intensive use
 Impact sound reduction	ISO 10140			Approx. ΔL _w 20 dB
 Sound absorption	EN ISO 354			Approx. 0.20 α _w
 Thermal resistance	ISO 8302			Approx. 0.10 m ² K/W
 Fireclass	EN 13501-1			Bfl - s1






Art Weave by Fletco®

T800000 - Weave TEXTiles® series



Certifications

	Standard	 Broadloom w/Textile	 Broadloom w/Felt	 Tiles
CE	EN 14041			0809-CPR-19006044-C8
DOP	EN 14041			1118#19006044-C8
IACG	EN 16516			Compliant
M1				Compliant
GUI				Compliant
GUT				Compliant
EPD - GWP A1-A3	ISO 14025 EN 15804+A2			8.6 kg CO ₂ - Eq
PEF - LCA Scope 3 CO ₂ - Eq according to EU PEF Standard				10.6 kg CO ₂ - Eq
Reach				Compliant
BREEAM NOR				Compliant
Recycled content				100% recycled backing



As we continuously improve our products and testing procedures, any above declaration is subject to amendments without prior notice. For the latest technical specifications, installation and maintenance guide visit:

www.yorkshore.com

Yorkshore Commercial Interiors

3551 W 1st St. Sanford, FL 32771

866-996-7563 | Yorkshore@Yorkshore.com