


328300



328160



328220



328260



328300



328330




328350




328370



328390



328650



328850

328000 / T328000

COM 1000

– quality and functionality for all times

COM 1000, with its stringently simple design, embodies a timeless carpet where high quality plays the leading role alongside functionality beyond the ordinary. The classic expression carries reminders of cobblestone paving, which has had significant architectural importance over time with its patterned surfaces in urban spaces. Available both as broadloom, square carpet tiles, ZigZag-Tiles[®], and as LockTiles[®].

Available in 10 timeless colours. Felt backing from +200 m².

COM 1000

328000 / T328000




Technical data

	Standard	 Broadloom w/Textile	 Broadloom w/Felt	 Tiles
Type of manufacture	ISO 2424	Woven	Woven	Woven
Structure	ISO 2424	Loop pile	Loop pile	Loop pile
Pile material	ISO 2424	100% PA6	100% PA6	100% PA6
Dye method		Solution dyed	Solution dyed	Solution dyed
Primary backing	ISO 2424	PET	PET	PET
Secondary backing	ISO 2424	rPET Textile	rPET Felt	TEXtiles®
 Dimensions/Width	ISO 3018	Approx. 400 cm	Approx. 400 cm	50 x 50 cm (5 m²/box)
Surface pile thickness	ISO 1766	Approx. 2.00 mm	Approx. 2.00 mm	Approx. 2.00 mm
 Total thickness	ISO 1765	Approx. 3.00 mm	Approx. 4.00 mm	Approx. 4.5 mm
Total pile mass	ISO 2424	Approx. 400 g/m²	Approx. 400 g/m²	Approx. 400 g/m²
 Total mass	ISO 8543	Approx. 1,750 g/m²	Approx. 2,100 g/m²	Approx. 3,100 g/m²
Stitch rate	ISO 1763	Approx. 164,000 /m²	Approx. 164,000 /m²	Approx. 164,000 /m²
 Antistatic	ISO 6356	≤ 2 kV	≤ 2 kV	≤ 2 kV
 Classification for use	EN 1307	23 Domestic - Intensive use	23 Domestic - Intensive use	23 Domestic - Intensive use
 Classification for use	EN 1307	33 Commercial - Heavy use	33 Commercial - Heavy use	33 Commercial - Heavy use
 Luxury rating class	EN 1307	LC1	LC1	LC1
 Dimensional stability	EN 986	-	-	≤ 0,2 %
 Castor chair suitability	EN 985	Intensive use	Intensive use	Intensive use
 Stair suitability	EN 1963	Intensive use	Intensive use	Intensive use
 Impact sound reduction	ISO 10140	Approx. ΔL _w 14 dB	Approx. ΔL _w 18 dB	Approx. ΔL _w 20 dB
 Sound absorption	EN ISO 354	Approx. 0.10 a _w	Approx. 0.15 a _w	Approx. 0.20 a _w
 Thermal resistance	ISO 8302	Approx. 0.06 m² K/W	Approx. 0.09 m² K/W	Approx. 0.10 m² K/W
 Fireclass	EN 13501-1	C _{fl} – s1	C _{fl} – s1	B _{fl} – s1


Recommended tile installation




LockTiles®



ZigZag-Tiles®



Square



COM 1000

328000 / T328000



Certifications

	Standard	 Broadloom w/Textile	 Broadloom w/Felt	 Tiles
CE	EN 14041	0809-CPR-19006044-C3	0809-CPR-19006044-C3	0809-CPR-19006044-C7
DOP	EN 14041	1118#19006044-C3	1118#19006044-C3	1118#19006044-C7
IACG	EN 16516	Compliant	Compliant	Compliant
M1		Compliant	Compliant	Compliant
GUI		Compliant	Compliant	Compliant
GUT		Compliant	Compliant	Compliant
EPD - GWP A1-A3	ISO 14025 EN 15804+A2	8.13 kg CO ₂ - Eq	8.13 kg CO ₂ - Eq	8.85 kg CO ₂ - Eq
PEF - LCA Scope 3 CO ₂ - Eq according to EU PEF Standard		8.7 kg CO ₂ - Eq	9.2 kg CO ₂ - Eq	10.7-11.0 kg CO ₂ - Eq
Reach		Compliant	Compliant	Compliant
BREEAM NOR		Compliant	Compliant	Compliant
Recycled content		100% recycled backing	100% recycled backing	100% recycled backing



As we continuously improve our products and testing procedures, any above declaration is subject to amendments without prior notice. For the latest technical specifications, installation and maintenance guide visit:

www.yorkshore.com

Yorkshore Commercial Interiors
3551 W 1st St. Sanford, FL 32771
866-996-7563 | Yorkshore@Yorkshore.com