

Technical data

	Standard	 Broadloom w/Foam
Type of manufacture	ISO 2424	Tufted 5/32
Structure	ISO 2424	Loop pile
Pile material	ISO 2424	100% PP
Primary backing	ISO 2424	PP
Secondary backing	ISO 2424	Foam
 Dimensions/Width	ISO 3018	Approx. 400 & 500 cm
Surface pile thickness	ISO 1766	Approx. 3.00 mm
 Total thickness	ISO 1765	Approx. 7.00 mm
Total pile mass	ISO 2424	Approx. 550 g/m ²
 Total mass	ISO 8543	Approx. 2,300 g/m ²
Stitch rate	ISO 1763	Approx. 92,000 /m ²
 Antistatic	ISO 6356	≤ 2 kV
 Classification for use	EN 1307	22 Domestic - Moderate use
 Luxury rating class	EN 1307	LC1
 Impact sound reduction	ISO 10140	Approx. ΔL _w 25 dB
 Thermal resistance	ISO 8302	Approx. 0.13 m ² K/W
 Fireclass	EN 13501-1	E _{fl} – s1
CE	EN 14041	EN 14041:2004 17
DOP	EN 14041	DOP Loopy Home 525000
IAC	EN 16516	Compliant

As we continuously improve our products and testing procedures, any above declaration is subject to amendments without prior notice. For the latest technical specifications, installation and maintenance guide visit:

www.yorkshire.com