



T850001000

Sebastian Wrong

– form, flexibility, and creativity

An award-winning concept by the renowned British designer Sebastian Wrong, who also lends his name to the collection. The thoughtful design concept – based on the Nordic carpet tile – focuses on shape and flexibility, inspiring creativity. With laser-cut carpet tiles in no fewer than nine different shapes and five colour categories, Sebastian Wrong by Fletco[®] offers nearly limitless possibilities to create a unique flooring solution in the sublime quality that characterizes Fletco's contract carpets.

Available in 18 classic colours, grouped into five curated colour categories. Special colours from +200 m².



850001300




850001120




850001160



850001240




850001260



850001290



850001300



850001340



850001350




850001380



850001390



850001500



850001650



850001740



850001750




850001770



850001820



850001850


















850001860

Sebastian Wrong by Fletco®

T850000



Technical data

	Standard	 Broadloom w/Textile	 Broadloom w/Felt	 Tiles
Type of manufacture	ISO 2424			Woven
Structure	ISO 2424			Loop pile
Pile material	ISO 2424			100% PA66
Dye method				Continuous dyed
Primary backing	ISO 2424			PET
Secondary backing	ISO 2424			TEXtiles®
 Dimensions/Width	ISO 3018			By order
Surface pile thickness	ISO 1766			Approx. 2.80 mm
 Total thickness	ISO 1765			Approx. 5.00 mm
Total pile mass	ISO 2424			Approx. 550 g/m ²
 Total mass	ISO 8543			Approx. 3,000 g/m ²
Stitch rate	ISO 1763			Approx. 156,000 /m ²
 Antistatic	ISO 6356			≤ 2 kV
 Classification for use	EN 1307			23 Domestic - Intensive use
 Classification for use	EN 1307			33 Commercial - Heavy use
 Luxury rating class	EN 1307			LC1
 Dimensional stability	EN 986			≤ 0.2 %
 Castor chair suitability	EN 985			Intensive use
 Stair suitability	EN 1963			Intensive use
 Impact sound reduction	ISO 10140			Approx. ΔL _w 20 dB
 Sound absorption	EN ISO 354			Approx. 0.20 α _w
 Thermal resistance	ISO 8302			Approx. 0.10 m ² K/W
 Fireclass	EN 13501-1			Bfl – s1






Sebastian Wrong by Fletco®

T850000



Certifications

	Standard	 Broadloom w/Textile	 Broadloom w/Felt	 Tiles
CE	EN 14041			0809-CPR-19006044-C7
DOP	EN 14041			1118#19006044-C7
IACG	EN 16516			Compliant
M1				Compliant
GUI				Compliant
GUT				Compliant
EPD - GWP A1-A3	ISO 14025 EN 15804+A2			11.1 kg CO ₂ - Eq
PEF - LCA Scope 3 CO ₂ - Eq according to EU PEF Standard				14.0 kg CO ₂ - Eq
Reach				Compliant
BREEAM NOR				Compliant
Recycled content				100% recycled backing



As we continuously improve our products and testing procedures, any above declaration is subject to amendments without prior notice. For the latest technical specifications, installation and maintenance guide visit:

www.yorkshore.com

Yorkshore Commercial Interiors

3551 W 1st St. Sanford, FL 32771

866-996-7563 | Yorkshore@Yorkshore.com