

FLOORIDA


PRODUCT DETAILS

Product Type Glue Down LVP
Construction Vinyl Dryback Plank
Classification ASTM F1700-Class III, Type A-Smooth, Type B-Embossed
Overall Thickness 2.5 mm and 5 mm
Wear Layer 22 mil (0.55 mm)
Edge Profile Micro Bevel
Surface Finish UV Coating
Embossing Photo Match Embossing / Stone Embossing
Plank Size 7" W x 48" L
SQ. Feet Per Carton 2.5 mm Plank 34.67 sf/ctn - 5.0 mm Plank 21.34 sf/ctn
Pieces Per Carton 2.5 mm Plank 13 pcs - 5.0 mm Plank 8 pcs
Carton Per Pallet 2.5 mm Plank 85 ctn/plt - 5.0 mm Plank 70 ctn/plt
Installation Method 2.5 mm Glue Down - 5.0 mm Looselay and Glue Down



TECHNICAL PROPERTIES

INTERNATIONAL
Standards Worldwide



Dimensional Stability	ASTM F2199 Passes $\leq 0.2\%$ / lineal ft. (305 mm)
Curling	ISO 23999 Passes $\leq 2\text{mm}$
Static Load	ASTM F970 Passes $\leq 0.005"$ (0.13mm)
Flexibility	ASTM F137 Passes- 1" mandrel passed
Residual Indentation	ASTM F1914 Passes Average: $\leq 8\%$ Max 10%
Resistance to Chemicals	ASTM F925 Passes No more than a slight change in surface
Critical Radiant Flux	ASTM E648 Passes Class I: $\geq 0.45 \text{ W/Sq.cm}$
VOCs/TVOCs, Formaldehyde	CDPH/EHLB Method Compliant
Substances of Very High Concern	REACH SVHC 191 Passes Per Substance: $\leq 0.1\%$ w/w
Heavy Metals	ASTM F963 Passes
Phthalates	ASTM D7823 Passes CPSC-CH-C1001-9.3
Slip Resistance	EN14041 - Result: Class DS

SUSTAINABILITY & WARRANTIES



Material Clean Recycle W/O DOTP
Certification Floor Score® Certified

Warranties Lifetime Residential & 20-Year Commercial

