


FLOORTRESS

PRODUCT DETAILS

Product Type	Gluedown L VP & L VT
Construction	Vinyl Gluedown Plank/ Vinyl Gluedown Tile
Classification	ASTM F1700-Class III, Type A-Smooth, Type B-Embossed 3mm (.12")
Overall Thickness	3.00mm (0.118")
Wear Layer	30 mil
Edge Profile	Micro Bevel
Surface Finish	UV Coating
Embossing	Photo Match Embossing / Stone Embossing
Plank Size	7" W x 48" L (177.8 mm x 1219.2 mm)
Tile Size	12" W x 24" L (304.8 mm x 609.6 mm)
SQ. Feet Per Carton	Plank 35 sf/ctn I Tile 36 st/ctn
Pieces Per Carton	Plank 35 I Tile II
Weight Per Carton	Plank 36.38 lbs I Tile 37.48 lbs
Carton Per Pallet	Plank 65 I Tile 60
Installation Method	Full Spread



TECHNICAL PROPERTIES



Dimensional Stability	ASTM F2199 Passes $\leq 0.2\%$ / lineal ft. (305 mm)
Curling	ISO 23999 Passes $\leq 2\text{mm}$
Static Load	ASTM F970 Passes $\leq 0.005"$ (0.13mm)
Flexibility	ASTM F137 Passes- 1" mandrel passed
Residual Indentation	ASTM F1914 Passes Average: $\leq 8\%$ Max 10%
Resistance to Chemicals	ASTM F925 Passes No more than a slight change in surface
Critical Radiant Flux	ASTM E648 Passes Class I: $\geq 0.45 \text{ W/Sq.cm}$
VOCs/TVOCs, Formaldehyde	CDPH/EHLB Method Compliant
Substances of Very High Concern	REACH SVHC 191 Passes Per Substance: $\leq 0.1\% \text{ w/w}$
Heavy Metals	ASTM F963 Passes
Phthalates	ASTM D7823 Passes CPSC-CH-C1001-9.3
Slip Resistance	EN14041 - Result: Class DS
IIC Rating	ASTM E492 & ASTM E989 Result: 66
STC Rating	ASTM E90 & ASTM E413 Result: 67

SUSTAINABILITY & WARRANTIES



Material Certification	Clean Recycle W/O DOTP Floor Score® Certified
-------------------------------	--

Warranties	Lifetime Residential & 20-Year Commercial
-------------------	---

